

WABCO ABS & RSS Kits provided by Sealco are identified with an alphanumeric part number. The individual numbers or letters, along with their positions & spaces, explain which components are in the Kits. The matrix below & the ABS System Kit Maker on our website allow you to construct a Kit for your specific application.

As an example, the individual numbers &/or letters in our ABS Kit # **21 2 10 FS** would relate to and be explained by the columns below.

1st & 2nd Digits	3rd Digit	4th Digit	5th Digit	6th Digit	7th, 8th & 9th Digits
ECU/Valve Assembly (& Relay Valve)	Power Cable	ABS Remote Vlv Cable RSS+ Distance Sensor	Sensor Extension Cables (2 Each)	Sensor Extension Cables (2 Each)	Suffix Codes
21 = 2S/1M 400 500 101 0	1 = 449 326 005 0 1.6'	Blank = No Cable	1 = 449 713 018 0 5.9'	1 = 449 713 018 0 5.9'	F = Control Line Filter 432 500 005 0
22 = 2S/2M 400 500 102 0	2 = 449 326 010 0 3.3'	1 = 894 606 275 2 1.3'	2 = 449 713 030 0 9.8'	2 = 449 713 030 0 9.8'	L = Long Sensors & Clips 2 or 4 - 441 032 809 0 2 or 4 - 894 501 001 4
23 = 2S/2M 400 500 103 0	3 = 449 326 030 0 9.8'	2 = 449 441 015 0 4.9'	3 = 449 713 050 0 16.4'	3 = 449 713 050 0 16.4'	R = Diagnostic Lead RSS+ 449 639 030 0
24 = 2S/1M 400 500 104 0	4 = 449 326 040 0 13.1'	3 = 449 441 030 0 9.8'	4 = 449 713 070 0 23.0'	4 = 449 713 070 0 23.0'	
42 = 4S/2M 400 500 103 0	5 = 449 326 047 0 15.4'	4 = 449 441 060 0 19.7'	5 = 449 713 090 0 29.5'	5 = 449 713 090 0 29.5'	S = Short Sensors & Clips 2 or 4 - 441 032 808 0 2 or 4 - 894 501 001 4
43 = 4S/3M 400 500 103 0 & 472 195 033 0	6 = 449 326 060 0 19.7'	7 = 449 441 080 0 26.2'	6 = 449 713 008 0 2.6'	6 = 449 713 008 0 2.6'	
1P = 2S/1M 400 500 106 0	7 = 449 328 030 0 9.8'	8 = 449 441 110 0 36.1'	7 = 449 713 120 0 39.4'	7 = 449 713 120 0 39.4'	T = Diagnostic Tool ABS 2237 Z 1222
2P = 4S/2M 400 500 105 0	8 = 449 364 142 0 1.3'	A = 449 811 020 0 6.6' & 441 050 100 0, 105 100 002 0, 441 901 715 4	8 = 449 713 170 0 55.8'	8 = 449 713 170 0 55.8'	
3P = 4S/3M 400 500 105 0 & 472 195 033 0	9 = 449 364 143 0 3.3'	B = 449 811 030 0 9.8' & 441 050 100 0, 105 100 002 0, 441 901 715 4	9 = 449 713 013 0 4.3'	9 = 449 713 013 0 4.3'	W = Straight Sensor & Clip 2 or 4 - 441 032 334 0 2 or 4 - 894 501 001 4
1R = 2S/1M 480 110 001 0	0 = 449 364 150 0 13.1'		A = 449 723 018 0 5.9'	A = 449 723 018 0 5.9'	
2R = 2S/2M 480 107 001 0	A = PEC4 08 & #1 9.6'		B = 449 723 030 0 9.8'	B = 449 723 030 0 9.8'	NOTE: All RSS Systems must contain a 432 500 005 0 Control Line Filter for Warranty Purposes
4R = 4S/2M 480 107 001 0	B = PEC4 08 & #2 11.3'		C = 449 723 051 0 16.7'	C = 449 723 051 0 16.7'	
	C = PEC4 35 & #1 36.6'		D = 449 723 120 0 39.4'	D = 449 723 120 0 39.4'	
	D = PEC4 35 & #2 38.3'		E = 449 765 018 0 5.9'	E = 449 765 018 0 5.9'	
	E = PEC4 48 & #1 49.6'		F = 449 765 030 0 9.8'	F = 449 765 030 0 9.8'	
	F = PEC4 48 & #2 51.3'		G = 449 765 051 0 16.4'	G = 449 765 051 0 16.4'	
	G = PEC4 64 & #1 65.6'				
	H = PECW 18 & #1 19.6'				
	J = PECW 35 & #1 36.6'				
	K = PECW 48 & #1 49.6'				
	L = PEC4 20 & #1 21.6'				
	M = 449 328 110 0 36.1'				
	V = 449 351 010 0 3.3'				
	W = 449 351 047 0 15.4'				

Yellow indicates RSS component.