



Sealco warrants its air valve products to be free from defects in material and workmanship under normal use and service for thirty-six (36) months from their date of manufacture. Sealco will, at its option, either repair, replace or credit the net purchase price of any Sealco air valve product that they find defective upon inspection. All warranty claims must be made in writing to Sealco and their return authorized by the issuance of a Returned Goods Authorization (RGA) number. All air valve products involved in warranty claims must be returned to Sealco for inspection. Warranty returns must be shipped prepaid & separate from any other items to Sealco Commercial Vehicle Products, 215 East Watkins Street, Phoenix, Arizona 85004, Attention: Warranty Department. Sealco will not extend any warranty or assume any liability for Sealco products repaired, rebuilt or manufactured by another party. All decisions made by Sealco concerning warranty issues are final.

This warranty shall not apply to any Sealco air valve product which: 1) has evidence of internal contaminants such as debris, sealant or additives, 2) has been employed in other than normal use or service, 3) has not been properly maintained, 4) has been altered, repaired or replaced in a harmful or unauthorized manner, 5) has been rebuilt by someone other than Sealco, 6) has been subjected to misuse, negligence, accident or mechanical damage including the use of additives in the air brake system or 7) has suffered impact or shock greater than that ordinarily encountered in the service for which the valve was designed or intended. The alteration, repair, or replacement by Sealco of an air valve product for any reason will not extend this warranty.

There is no other warranty or liability, expressed or implied, applicable to Sealco air valve products and in no event shall Sealco be liable for any consequential or special damages resulting from the use of Sealco valve products.

**CAUTION!**  
*THE USE OF ADDITIVES IN THE AIR BRAKE SYSTEM IS NOT RECOMMENDED AS  
THEY CAN BE HARMFUL TO THE PERFORMANCE OF THE AIR BRAKE VALVES*